

Trysky s nastavitel. výšečí pro rozprašovací postřik.

nastavení výšeče	prac. tlak bar	dostř. m	průtok vody l/s	průtok vody m ³ /hod	srážková výška mm/hod ■ ▲	
------------------	----------------	----------	-----------------	---------------------------------	------------------------------	--

● MAN, ARC 7 - plynule nastavitelná výšeč 25 - 360°						
360°	1.4	1.8	0.09	0.31	92.0	107
	1.7	2.1	0.10	0.35	78.0	90.0
	2.1	2.1	0.12	0.44	97.0	112
270°	1.4	1.8	0.06	0.23	92.0	107
	1.7	2.1	0.07	0.26	78.0	90.0
	2.1	2.1	0.09	0.33	97.0	112
180°	1.4	1.8	0.04	0.16	92.0	107
	1.7	2.1	0.05	0.18	78.0	90.0
	2.1	2.1	0.06	0.22	97.0	112
90°	1.4	1.8	0.02	0.08	92.0	107
	1.7	2.1	0.03	0.09	78.0	90.0
	2.1	2.4	0.03	0.11	97.0	113

nastavení výšeče	prac. tlak bar	dostř. m	průtok vody l/s	průtok vody m ³ /hod	srážková výška mm/hod ■ ▲	
------------------	----------------	----------	-----------------	---------------------------------	------------------------------	--

● MAN, ARC 15 - plynule nastavitelná výšeč 25 - 360°						
360°	1.4	4.3	0.20	0.70	38.0	44.0
	1.7	4.6	0.22	0.80	38.0	44.0
	2.1	4.6	0.23	0.84	40.0	47.0
270°	1.4	4.3	0.15	0.53	38.0	44.0
	1.7	4.6	0.17	0.60	38.0	44.0
	2.1	4.6	0.18	0.63	40.0	47.0
180°	1.4	4.3	0.10	0.35	38.0	44.0
	1.7	4.6	0.11	0.40	38.0	44.0
	2.1	4.6	0.12	0.42	40.0	47.0
90°	1.4	4.3	0.05	0.18	38.0	44.0
	1.7	4.6	0.06	0.20	38.0	44.0
	2.1	4.6	0.06	0.21	40.0	47.0

● MAN, ARC 10 - plynule nastavitelná výšeč 25 - 360°						
360°	1.4	2.7	0.09	0.31	41.0	47.0
	1.7	3.0	0.09	0.35	38.0	44.0
	2.1	3.0	0.12	0.44	48.0	55.0
270°	1.4	2.7	0.06	0.23	41.0	47.0
	1.7	3.0	0.07	0.26	38.0	44.0
	2.1	3.0	0.09	0.33	48.0	55.0
180°	1.4	2.7	0.04	0.16	41.0	47.0
	1.7	3.0	0.05	0.18	38.0	44.0
	2.1	3.0	0.06	0.22	48.0	55.0
90°	1.4	2.7	0.02	0.08	41.0	47.0
	1.7	3.0	0.03	0.09	38.0	44.0
	2.1	3.0	0.03	0.11	48.0	55.0

● MAN, ARC 17 - plynule nastavitelná výšeč 25 - 360°						
360°	1.4	4.9	0.24	0.88	37.0	43.0
	1.7	5.2	0.28	1.02	38.0	44.0
	2.1	5.5	0.30	1.09	41.0	47.0
270°	1.4	4.9	0.18	0.66	37.0	43.0
	1.7	5.2	0.21	0.77	38.0	44.0
	2.1	5.5	0.23	0.82	41.0	47.0
180°	1.4	4.9	0.12	0.44	37.0	43.0
	1.7	5.2	0.14	0.51	38.0	44.0
	2.1	5.5	0.15	0.55	41.0	47.0
90°	1.4	4.9	0.06	0.22	37.0	43.0
	1.7	5.2	0.07	0.26	38.0	44.0
	2.1	5.5	0.08	0.27	41.0	47.0

● MAN, ARC 12 - plynule nastavitelná výšeč 25 - 360°						
360°	1.4	3.4	0.14	0.48	43.0	50.0
	1.7	3.7	0.14	0.51	37.0	43.0
	2.1	3.7	0.18	0.65	48.0	56.0
270°	1.4	3.4	0.10	0.36	43.0	50.0
	1.7	3.7	0.11	0.38	38.0	44.0
	2.1	3.4	0.14	0.49	48.0	56.0
180°	1.4	3.4	0.07	0.24	43.0	50.0
	1.7	3.7	0.07	0.26	38.0	44.0
	2.1	3.7	0.09	0.33	48.0	56.0
90°	1.4	3.4	0.03	0.12	43.0	50.0
	1.7	3.7	0.04	0.13	38.0	44.0
	2.1	3.7	0.05	0.16	48.0	56.0



Konstrukčně identické trysky HUNTER a NELSON s nastavitelnou výšečí jsou vyráběny pod tímto označením :

M.A.N. 7,10,12,15,17 – ozn. firmy NELSON
A nebo **ARC** 7,10,12,15,17 – ozn. firmy HUNTER

Trysky jsou použitelné pro rozprašovací postřikovače PRO-SPRAY, I-SPRAY, SRS a Série 6300 firem HUNTER a NELSON.